Proxima Ultralight LS1 Projector
Technical and Functional Specifications

Display Technology	• 0.9" polysilicon TFT LCD x 3
Resolution	• SVGA (800 x 600)
Resolution Supported	• VGA (640 x 480) • SVGA (800 x 600) • XGA (1024 x 768, with Fit-to-View® intelligent digital scaling)
Number of Colors	• 16.7 million colors
Brightness	• 700 ANSI lumens (peak)
Contrast Ratio	• 100:1 ANSI; 200:1 full-on, full-off
Computer Compatibility	• IBM PC, PS/2, Pentium and compatibles • Apple Macintosh, Power Mac, PowerBook
Video Compatibility	• NTSC, NTSC 4.43, PAL, SECAM
Input Sources	• 1 computer, 1 video, 1 S-video, 1 audio (stereo)
H-Sync Range	• 15-80 kHz
V-Sync Range	• 50-100 Hz
Dot Clock	• 130 MHz
Horizontal Resolution	• 750 TV lines
Aspect Ratio	• Std: 4:3 - Wide: 16:9
Image Size (Diagonal)	• 1.7 ft. to 26.3 ft. (0.5 m to 8.0 m)
Projection Lens	• Motorized zoom lens 1.6:1 ratio • Focal length: 36 mm to 57.6 mm, f/2.3-3.0
Projection Distance	• 4.3 ft. to 39.3 ft. (1.3 m to 12 m)
Keystone Correction	• 11°
Projection Method	• front/rear, desktop/ceiling
Lamp (Life)	• 120 watt UHP (2,000 hours)
Audio	• 1 watt mono
Remote Control	• Proxima Laser F/X remote with mouse control and laser pointer
Dimensions	• 8.5 in. W x 12.4 in. L x 4.3 in. H • 21.5 cm W x 31.5 cm L x 10.9 cm H
Weight	• 8.4 lb. (3.8 kg)
Power Consumption	• 190 watts
Power Requirements	• 110V-240V at 50 Hz/60 Hz auto change
Operating Temperature (Sea Level)	• 41-95° F (5-35° C)
On-Screen Languages	• English, Japanese, German, French, Italian, Spanish
Audible Noise	• <47db
Approvals	• FCC Class A (U.S.), UL, C-UL (Canada), CE (Europe)
Warranty	• Two years parts and labor (excluding lamp)

Copyright © 1997-2004 InFocus Corporation.
All Rights Reserved.